

DISPLAY

HI-END SERIES



HIGH-END INTERACTIVE DISPLAY



ANGUSTOS PRESENTATION SWITCH

ANGUSTOS flexible presentations switches are customized with many unique features to meet various demands from traditional presentation devices switching to advanced collaboration in corporate or education usage.

This series features user friendly control methods with plug-and-play principal. This even support the wireless touch back on interactive whiteboard/touch screen, support up to 4 split screen view at the same time for collaboration presentation.

Future-proof with Type-C connector for direct or wireless dongle help to eliminate messy cable routing in the meeting room. The series also support corporate rate data security with dual network, encryption on both input and outputs plug-in.



ANGUSTOS APS SERIES

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



WIRELESS PRESENTATION SWITCH

Model : AWP-0401M

FEATURES

- Wireless presentation switch with multiple connections
- Direct connection to device, no cable messy - up to 20m
- Wireless content input up to 1080P, HDMI 2.0 output
- Support native wireless mirroring (Airplay, Miracast, Chromecast)
- Support plug-in-display HDMI/Type-C dongles
- Support Android, MAC and Windows APP
- Support MPiP™ 4 split screen view. Seamless 20ms switch
- Support wireless touch back on interactive whiteboard/touch screen
- Best-in-class data security with dual network (Gigabit/100Mbps)
- AES / WPA2 encryption for LAN connection.
- Power over Ethernet (POE) supported
- OSD control with preview function.
- Support whiteboard and annotation.
- 3.5mm audio port for speaker set up
- RS-232 support (phoenix)



SYSTEM SPECIFICATION

HDMI output	HDMI female x 1	Latency	20 - 100 ms
Video output resolution	3840 x 2160 @ 60Hz	WIFI Data Rate	1200Mbps
	1920 x 1080 @ 60Hz	Wireless protocol	IEEE 802.11 b/g/n/ac
HDMI Standard	HDMI 1.4 / 2.0	Frequency	2.4 GHz & 5 GHz
Wireless resolution	1080p@60Hz / 30Hz	WIFI Antenna	MIMO 2x2
HDCP Standard	HDCP 1.4 / 2.2	WIFI Encryption	AES WPA PSK, WPA2 PSK
Audio Out	3.5mm female x 1	Control Method	Web GUI, Telnet, RS-232
Ethernet	RJ-45 x 2 (Gigabit / 100Mbps)	PoE support	IEEE802.3af
USB	USB 3.0 x 1	Power	DC 12V / POE
	USB 2.0 x 1/Type-C (2.0) x 1	Dimension	165 x 100 x 24.5mm
	Anti-glare , 7H hardness	Weight	0.4 kg
Audio Input	AirPlay, Windows, WMH	Power consumption	10 ~ 15 Watt
Audio Output	3.5 mm Audio out	Temp (Working)	0~45°C
	HDMI audio out	Temp (Storage)	-20~60°C
Control Port	3.5mm Phoenix / RS-232	Humid (Working/Storage)	0-90% RH - non condensing
Total video on screens (max)	16 (4 split + 12 thumbnail)	Power Rate for adapter	100 - 240 VAC. 50-60Hz
Simutaneous connection	16	Wireless distance (Optimal)	20m with 5GHz 30m with 2.4Ghz
Playback frame rate	20 - 60 FPS		

WIRELESS PRESENTATION SWITCH

Model : AWP-0401M

CONNECTION DIAGRAM



PC



Laptop



Tablet



Mobile



HDMI Dongle



Type - C Dongle



Up to 20m (open area)



AWP - 0401M front



AWP - 0401M back



HDMI

RJ-45 (Cat5e/6)

POE Switch