ANGUSTOS

DESKTOP PROFESSIONAL
KVM SWITCH SERIES

AD-V21L

2 Port VGA KVM Switch
Desktop KVM Switch

Overview

Angustos AD-V21L Desktop KVM Switch is optimized for high density office in modern workstation set up.

A KVM Switch with 2 VGA and supports computers with USB interfaces via cables. All packed in a small size desktop metal housing. The small size design ultilized for narrow space for personal or office / SOHO uses. The AD-V21L can control up to 02 computers.

In addition, the AD-V21L included the computer selection via front panel pushbuttons, hotkeys combination. With all of the technology involved, the AD-V21L Desktop KVM Switch has gone beyond the expectations and requirements for a modern digital usage, which including : small size - space optimization, exceptional display quality, easy to install, extreme versatility.

Features

High Density Utilization

- One USB console controls 2 ports computers/servers; Simulation function of keyboard and mouse built-in
- Easy installation , nosoftware required
- Computerselection via button on front panel or hotkey on keyboard
- OS support: Windows, Vista, LINUX, Mac and Free BSD
- Auto-scan function to monitorcomputer operation
- Hot plug-gable to add orremove computers without powering down.

Installation Flexibility

- No software required - Plug and Play
- Front USB peripheral for keyboard / mouse / flash usb / printer support.
- Supports hot-plugging
- No power adapter needed - KVM Switch unit use USB Power.
- Power adapter - Optional.

Compatible Product

AR-V08L

SHORT DEPTH
RACK KVM SWITCH

AR-V16L

SHORT DEPTH
RACK KVM SWITCH

AIP-C

IP MODULE CARD

AD-V21L FRONT VIEW

AD-V21L REAR VIEW

- Raise efficiency
- Multiple Connection
- Saving time
- Cascadable
- Saving Cost
- Plug and Play

Angustos

Angustos was founded in 2000 and is now regarded as one of the foremost manufacturers of digital and analogue KVM solutions.

For more than 20 years our customers have been convinced by our core competencies in extending, switching and distributing standardised computer signals.

We are committed to established international standards. We can provide customers with complete Datacenter solutions as well as OEM/ODM services. We can cover even from medium to small business, factory & industrial, military & government, home office & personal use.

SPECIFICATION

ANGUSTOS

KVM SWITCH MODULE

Direct PC connection	02
Port Selection	Button, Hot Key
Console Connector	VGA x 1
	USB Type A x 4 *
	3.5mm Speaker x 1
	3.5mm Mic x 1
KVM Connector	VGA with 3.5mm Speaker x 2
	3.5mm Mic x 2
Video Resolution	2048 x 1536(max) ; DDC2B
Power*	DC Jack - Optional
Switch button	Button x 2
Reset Switch	Semi recessed button
Status LEDs - Nixie Tube	Green led (Selected Port)
	Red led (Online Port)
Switch hotkey (default)	CTL + CTL

OPERATIONAL SPECIFICATION

Operating Temp	10°C - 50°C
Storage Temp	-20°C - 60°C

PHYSICAL SPECIFICATION

Housing	Metal
Dimension	86 x 86 x 26.5 mm
Weight	0.57 Kg

** Power adapter is not included with the KVM Unit.*
Power adapter is used when user use USB-PS/2 converter.

**USB compatibility : Please use normal keyboard and mouse for best connection. Gaming or multimedia keyboard is not supported.*

CONNECTION DIAGRAM