

VGA USB - PS/2 Combo KVM Cable AR-CC02L / AR-CC03L / AR-CC05L / AR-CC10L

FEATURES

- Server-end: VGA + USB-A (or PS/2)
- KVM port: 3in1 SPHD (Keyboard / Video / Mouse)
- Length :
 - AR-CC02L : 1.8 meter
 - AR-CC03L : 3 meter
 - AR-CC05L : 5 meter
 - AR-CC10L : 10 meter(Please consult with ANGUSTOS sales representative for 10m cable)
- The cascade mode description is as follows:
 1. A cascaded KVM switch can be connected in two ways by using a USB KVM cable or a PS/2 KVM cable. Connect to the upper-level KVM switch by using console connection (Check Connection Diagram).
 2. The number of computers connected to each level can be free to increase or decrease according to requirement.
 3. Between the cascade connection devices, it can be optional for remote control, can also be handed over from the top level and remote level as a unified control operations.



SPECIFICATIONS

To PC / Server Interface	
VGA	HDB-15 Male
PS/2	6 pin mini-DIN Male
USB	USB Type A Male
To KVM Switch Interface	
KVM Port	SPHD-15 Male

COMPATIBLE CHART

Desktop KVM SWITCH	AD-VxxL Series
Rackmount KVM SWITCH	AR-VxxL Series
LCD KVM SWITCH	AR-VXxxL Series
	AR-VXxxLS Series
	*** xx can be 04 - 08 - 16 port
	X can be 7 for 17 inch or 9 for 19 inch

CONNECTION DIAGRAM

AR-VX16L Series (Example)

