

19 Inch LCD 16 port VGA KVM Dual Rail AL-DV916L

FEATURES

- ☐ 1U height, suitable for 19" standard cabinet installation and metal structure.
- ☐ With dual rail structure, LCD screen and keyboard can be pulled out separately.
- ☐ One control platform can control 16 computers by direct connection.
- ☐ Support multiple operating systems:
WIN95/98/98SE/ME/200/XP, WIN 7, WIN NT, UNIX, LINUX.
- ☐ IP optional (IP card could be installed inside KVM module).



LCD MONITOR

Ratio	19" Screen, 4:3
Video	Wide AHVA TFT-LCD
Visible Square	376.32(H) x 301.06(V)
Resolution	1280*1024 @60HZ(Optimum)
	1920*1200@60HZ(Max)
Color	16.7M, True 8 bit
Contrast	1000 : 1 (Typ)
Back light	LED Screen
Pixel Pitch	294*294um
MTBF	100,000 hours
Keyboard	100 Keys, Detachable
Compatible	Windows /Sun/Unix/Linus
Mouse	Touchpad
Mouse Resolution	>1000 dots/inch (40x40/mm)
MTBF	1,000,000 Press
Installation Dimension	645 x 442.4 x 44.5mm
Weight	11.09kg

KVM SWITCH MODULE

Direct PC connection	16
Maximum PC Connection	256
Port Selection	OSD, Button, Hot Key, IP (Optional)
Console Connector	DB-37 Pins
Switch Module Port	16 x VGA DB15, Female Blue
Network Port	1 x RJ45(Optional)
Power	DC Jack
Switch button	Panel Digital Keys
Reset Switch	Panel Function Keys
IP Module Reset	1 x semi-embedded key
IP Module Default	1 x semi-embedded key
Keyboard/Mouse	USB, PS/2
Resolution (Max)	1920 x 1200 @ 60HZ
Operating temperature	-10-50°C
Storage temperature	-20-60°C
Humidity	0-80%RH, No Condensation
Housing	Metal
Dimension	158*439*44.5mm
Weight	5.23kg