

AL-V18516FD

16 PORT - 19" rackmount PS/2-USB VGA
Single Rail WideScreen Full HD LCD KVM Switch

Overview

Angustos AL-V18516FD LCD KVM Console Drawer is optimized for high density Rack in modern Data Center.

Integrating a 18.5" LED screen, keyboard and mouse pad in a 1U rackmountable sliding housing. The compact design console is utilized for extreme narrow space and super densed area. The AL-V18516FD can be installed and connected with Angustos KVM Switch or other brand KVM for convenience configuration. The AL-V18516FD can control up to 16 computers; with 16 additional KVM switches are cascaded, a single AL-V18516FD LCD KVM Switch can control up to 256 computers.

In addition, the AL-V18516FD included an additional hot-pluggable USB port that supports other keyboard and mouse for back-up. With all of the technology involved, the AL-V18516FD LCD KVM Console has gone beyond the expectations and requirements for a modern Data Center use, which including : short space optimization, exceptional display quality, easy to install, extreme versatility.



AL-V18516FD FRONT VIEW



AL-V18516FD REAR VIEW

Features

High Density Utilization

- Front USB for back up mouse-keyboard.
- LCD KVM console with an 18.5" LED-backlit 16:9 LCD monitor in a single rail design.
- Short-depth overall size allowing user to work with in condensed space of high density Rack
- Cross-based keyboard with integrated Digital & E-switch keys.
- Aluminum-magnesium upper shelf.
- OSD button : One touch access.
- Certificate : CE , FCC , RoHS

Flexible compatibility

- Superior video quality – up to 1920x1080 ; DDC2B. Back up 2nd Console ports.
- Compatible with Angustos and other brands KVM Switches. Support Auto Scan.
- Cascade up to 256 computers from a single console (With compatible KVM Switches).
- Auto PS/2 and USB interface sensing.
- Operates with all software and operating systems including all Windows versions, DOS, Linux. (Unix, Sun OS, Mac OS optional).
- Keyboard Language supports: English (UK), English (US), German (GER.) Japanese, Korean, Russian, Swedish, Chinese.
- Two level password security (Optional)

Installation Flexibility

- Standard rack mount kit included
- No software required - Plug and Play
- Supports hot-plugging



Saving time



Raise efficiency



Saving Cost



18.5 Inch display
(16:9)



Plug and Play



Password
Protected

Compatible Product



SHORT DEPTH
RACK KVM SWITCH

AR-V08D



SHORT DEPTH
RACK KVM SWITCH

AR-V16D



HIGH - DENSITY
RACK KVM SWITCH

AR-UV32D

Angustos

Angustos was founded in 2000 and is now regarded as one of the foremost manufacturers of digital and analogue KVM solutions.

For more than 20 years our customers have been convinced by our core competencies in extending, switching and distributing standardised computer signals.

We are committed to established international standards. We can provide customers with complete Datacenter solutions as well as OEM/ODM services. We can cover even from medium to small business, factory & industrial, military & government, home office & personal use.

KEYBOARD & MOUSE

Keyboard	100 Keys
	Multiple Languages Option
Compatible	Win/Linux (Sun/Unix/Mac Option)
Mouse	Touchpad
Mouse Resolution	>1000 dots/inch (40x40/mm)
MTBF	1,000,000 Press

KVM SWITCH MODULE

Direct PC connection	16
Maximum PC Connection	256
Port Selection	OSD, Button, Hot Key
Console Connector	DB-15 Pins , USB , PS/2
KVM Connector	DB-15
Power	DC 12V/AC 100-240V 50/60Hz
Switch button	Panel Digital Keys
Reset Switch	Panel Function Keys
Status LEDs	Nixie Tube (Selected Port)
	Red led (Online Port)
Server Interface	PS/2 , USB
Cascadable	Support. Max 3 Levels

LCD MONITOR

Size / Ratio	18.5" / 16:9
Video	Wide AHVA TFT - LCD
Visible Square	337.92 H x 270.336 V
Resolution	1920 x 1080 @ 60Hz (Optional)*
Color	16.7 Mil. , True 8 Bit
Contrast	1000 : 1 (TyP)
Back light / Brightness	LED / 300 nit (cd/m2)(400 nit optional)
Pixel Pitch	0.3 x 0.3 mm
MTBF	100,000 hours
Screen Rotation	110°

OPERATIONAL SPECIFICATION

Operating Temp	-10°C - 50°C
Storage Temp	-20°C - 60°C
Humidity	0-80%RH, No Condensation

PHYSICAL SPECIFICATION

Housing	Metal - Aluminum
Dimension LCD / KVM	59.5 x 48.2 x 4.3 mm
Weight LCD / KVM	~9.5kg
Power - Consumption	DC12V. 100-240V AC 50/60Hz 1W standby - 20W nominal

CONNECTION DIAGRAM

