



AL-V716LS

16-Port PS/2-USB VGA
Single Rail LCD KVM Switch

Overview

Angustos AL-V716LS LCD KVM Switch is optimized for high density Rack in modern Data Center.

Integrating a 17" LED screen, keyboard and mouse pad in a 1U rack mountable sliding housing. The short-depth design utilized for narrow space for short-rack mounting in condensed area. The AL-V716LS can control up to 16 computers; with 512 additional KVM switches are cascaded on two more level, a single AL-V716LS LCD KVM Switch can control up to 16384 computers.

In addition, the AL-V716LS included an additional hot-pluggable USB port that supports other keyboard and mouse for back-up. With all of the technology involved, the AL-V716LS LCD KVM Switch has gone beyond the expectations and requirements for a modern Data Center use, which including: short space optimization, exceptional display quality, easy to install, extreme versatility.

Features

High Density Utilization

- Front USB for back up mouse-keyboard.
- LCD KVM console with an 17" LED-backlit 4:3 LCD monitor in a single rail design.
- Short-depth overall size allowing user to work with in condensed space of high density Rack
- Slide Lock – secure the console drawer to remain firmly in slide position when not in use.

Flexible compatibility

- Superior video quality – up to 1280 x 1024 @60Hz; DDC2B; 16.7 Mil. Color.
- Cascade up to 16384 computers from a single console (With compatible KVM Switches)
- Auto PS/2 and USB interface sensing.
- Keyboard and mouse emulation (PS/2 and USB) for seamless switching.
- Computer selection with pushbuttons, hotkeys, and multilingual on-screen display (OSD).
- Two level password security.
- Triple DES encryption. ISO/IEC 18033-3: 2010:Part 3 Standard.
- Operates with all software and operating systems including all Windows versions, DOS, Linux, Unix, BSD, all Sun OS, all Mac OS and NetWare.
- Keyboard Language supports: English (UK), English (US), German (GER.) Japanese, Korean, Russian, Swedish, Chinese.

Installation Flexibility

- Standard rack mount kit included
- No software required - Plug and Play
- Firmware upgradable
- Supports hot-plugging
- Supports Over IP Module for Remote Control



Raise efficiency



Multiple Connection



Saving time



Cascadable



Saving Cost



17" Inch display (4:3)



Plug and Play



Password Protected

Compatible Product



AR-V08L

SHORT DEPTH
RACK KVM SWITCH



AR-V16L

SHORT DEPTH
RACK KVM SWITCH



AIP-C

IP MODULE CARD



AL-V716LS FRONT VIEW



Triple DES



AL-V716LS REAR VIEW

Angustos

Angustos was founded in 2000 and is now regarded as one of the foremost manufacturers of digital and analogue KVM solutions.

For more than 20 years our customers have been convinced by our core competencies in extending, switching and distributing standardised computer signals.

We are committed to established international standards. We can provide customers with complete Datacenter solutions as well as OEM/ODM services. We can cover even from medium to small business, factory & industrial, military & government, home office & personal use.

KEYBOARD & MOUSE

Keyboard	104 Keys, Detachable
	Multiple Languages Option
Compatible	Win/Sun/Unix/Linux/Mac
Mouse	Touchpad
Mouse Resolution	>1000 dots/inch (40x40/mm)
MTBF	1,000,000 Press

KVM SWITCH MODULE

Direct PC connection	16
Maximum PC Connection	16,384
Port Selection	OSD, Button, Hot Key, IP (Opt)
Console Connector	DB-15 Pins , RJ45 (IP Module), USB
KVM Connector	DB-15 Female x 16
Power	DC 12V/AC 100-240V 50-60Hz
Switch button	Panel Digital Keys
Reset Switch	Panel Function Keys
Status LEDs	Nixie Tube (Selected Port) Red led (Online Port)
Server Interface	PS/2 , USB
Auto Scan	Support
Security	Triple DES - 168bit encryption Two level password
Cascadable	Support cascade to max 3 levels
IP Module	Optional

LCD MONITOR

Size / Ratio	17" / 4:3
Video	SXGA TFT - LCD. DDC2B
Visible Square	337.92 H x 270.336 V
Resolution	1280 x 1024 @ 60Hz (Optimal) 1920 x 1200 @ 60Hz (Max)
Screen Rotation	120°
Color	16.7 Mil. , RGB 6bit + Hi_FRC
Contrast	1000 : 1 (Typ)
Back light / Brightness	LED / 300 nit (cd/m2) (400 nit optional)
Pixel Pitch	0.264 x 0.297 mm
MTBF	100,000 hours

OPERATIONAL SPECIFICATION

Operating Temp	-10°C - 50°C
Storage Temp	-20°C - 60°C
Humidity	0-80%RH, No Condensation

PHYSICAL SPECIFICATION

Shock	10G acceleration (11 ms duration)
Vibration	10-300Hz 0.5G RmS Random
Operating altitude	15,500 ft-35,000 ft
Dimension LCD / KVM	407x445x45 / 148.4x445x45mm
Weight LCD / KVM	6.15 kg / 4.96 kg

CONNECTION DIAGRAM

