



ANGUSTOS  
Next Generation Video Wall Display  
S55BO8LK

ANGUSTOS Inc.  
[www.Angustos.com](http://www.Angustos.com)  
Annandale, VA, USA

## Not just a typical display

Angustos LCD video wall displays ensure an impressive content illustration effect for multiple business applications. Smart design with dust-proof material and durable components ensure 24/7 operation.

Ultra-wide viewing angle provides exceptional display effect not just for offices, but also retail business uses of the product.




### Signal Interface



### DP - 4K version




### Glare Reflective



Special coating on the screen surface effectively reduces color distortion when using indoor with bright surrounding light.

Color active matrix TFT LCD Module using amorphous silicon TFT's (Thin Film Transistors) as active switching devices. The TFT LCD panel used for this module is adapted for a low reflection and higher color type.

### Dust-proof with IP5X



IP5X certification provides a completely dust-free screen and can illustrate contents in endless working hours. Suitable for Store and Shopping Mall or public spaces without the need for additional dust-resistant molding.

ADS Technology is applied for high display quality after long exposure in bright and dusty environments.

### Exceptional with 68,000 hours MTPF



Stunning performance with 68,000 hours MTPF allows a visual display 24/7 with extremely high response time (8 ms) in a long period of time.

The mounting option also provides a good support platform and easy to maintain surface for technicians when troubleshooting.

\*The life time is determined as the time which luminance of LED is 50% compared to the initial value at the typical LED current on condition of continuous operating in LCM state at  $25 \pm 2$  °C



# FEATURES

## 178° WIDE ANGLE VIEW

High contrast screen with WAPA™ (Wide Angle Pixel Application) features, Angustos Video Wall LCD series offer a wide view range for a wider application.



## THIN BEZEL AND THIN PROFILE

Impress viewer with ultra razor thin bezel to bezel, capture attention and illustrated stunning content. The slender design significantly reduces operational and installation space.



## BUILT-IN DAISY CHAIN VIDEOWALL PROCESSOR

Intelligent Control software control and configure multiple LCD displays through an RS232 or RJ45 connection (Regardless of the monitor's location ) to make the wall easier to set up and the status of all networked displays.

Through the display's built-in splicing function, it can support upto maximum of 15 x 15 (total 225 screens) to display the complete picture perfectly with or without external connection to Video Wall Processor unit.



## 4K UHD Video Wall\*

With industry-leading daisy chain technology, ANGUSTOS super narrow bezel displays are designed to display a stunning 4K UHD images and video.

The content is spread across a 2x2 video wall installation, allowing customer to conveniently create and enrich 4K video message \*.

\* Available on selected model

# SPECIFICATIONS

|                   |                                 |  |
|-------------------|---------------------------------|--|
| Panel             | Display Size                    | 55 inch  |
|                   | Resolution                      | 1920x1080  |
|                   | Bezel to Bezel                  | 0.86mm   |
|                   | Active area(HxW mm)             | 1209.6x680.4   |
|                   | Aspect Ratio                    | 16:9   |
|                   | Brightness (cd/m <sup>2</sup> ) | 500  |
|                   | Colour                          | 16.7M  |
|                   | Viewing Angle                   | 178°   |
|                   | Contrast Ratio                  | 4000:1   |
|                   | Backlight Life                  | 68000 hours  |
|                   | Surface Treatment               | Haze 25%   |
|                   | Hardness                        | 3H - Polarizer   |
|                   | Color Gamut                     | 72% . Gamma Scale 2.2  |
| Pixel Pitch (µm)  | 210 (H) x RGB x 630(V)          |  |
| Frequency (max)   | DCLK (f <sub>clk</sub> )        | 82 MHz   |
|                   | Horizontal (f <sub>h</sub> )    | 72.3 KHz   |
|                   | Total (f <sub>t</sub> )         | 63 Hz  |
| AV input / output | Video                           | HDMI 1.4 IN, HDMI 2.0 IN, DVI IN, VGA. (Optional : Display Port) |
|                   | Audio                           | Audio in, Audio out  |
|                   | USB                             | USB 2.0 for Firmware   |
|                   | Communication                   | RS232 input, RS232 output  |
| Power             | Power Consumpt                  | 160w   |
|                   | Input Voltage                   | 100V~240V(50/60Hz)   |
| Mechanical        | Unit size (LxWxH mm)            | 1213x684x123   |
|                   | Net weight (kg)                 | 28   |
|                   | Gross weight (kg)               | 33   |
| Environmental     | Working Temperature             | 0-50°  |
|                   | Operating Humidity              | 10-90%   |
|                   | Working Pressure                | 800-1114 hpa (Altitude:0-2000m)                                  |
| Accessories       | Included                        | Remote control, Power Cable, User Manual                         |

\*Information maybe changed without notice

# APPLICATION



SHOPPING - RETAIL



BUSINESS - CONFERENCE - HOSPITALITY



CONTROL CENTER

