



AP-V2OU4C19-M16A-LT

1 PHASE BASIC PDU SERIES
20 x Universal + 4 x C19 / 16A
MCCB/ IE-6O3O9 inlet

Overview

Angustos Basic PDU series deliver a simple yet reliable power to critical IT equipments inside your rack cabinet. Suitable for many type of applications with a wide range of configuration that suit every solutions.

Product Features

- * Simple with no configuration
- * Reliable with wide range of outlets
- * Cost efficient
- * Fully tested before delivery
- * Industrial MCCB for maximum protection
- * Lock outlets optional


Specification

AP-V2OU4C19-M16A-LT


Quantity of inlet	1
Voltage	
Current	16A
VA per Input (Load capacity)	3.68 (230V)
Frequency	50/60Hz
Over Current Protection	1x16A Magnetic Breakers
Materials	Aluminum shell+ ABS model
Power Cable Length	3m, 4mm ² H05V V-F cordset
Plug Type	IEC60309 1P + N + E, 32A, 250V, Splashproof IP44
Receptacle/Socket Type	20 x Universal 4 x C19
Maximum Output per Receptacle/Socket	10A for Universal 16A for C19

Standard Certified

- * Comply with: CE / EMC
 - EN 62368-1
 - EN 60950-1
 - EN 55022
 - EN 55024
 - IEC 61000-4-2: 2008
 - IEC 61000-4-3: 2006+A2: 2010
 - IEC 61000-4-4: 2004
 - IEC 61000-4-5: 2005
 - IEC 61000-4-11: 2004
 - RoHS - REACH



20 x Universal Outlet



4 x C19



IEC-6O3O9 inlet

Angustos

Angustos was founded in 2000 and is now regarded as one of the foremost manufacturers of digital and analogue KVM solutions.

For more than 20 years our customers have been convinced by our core competencies in extending, switching and distributing standardised computer signals.

We are committed to established international standards. We can provide customers with complete Datacenter solutions as well as OEM/ODM services. We can cover even from medium to small business, factory & industrial, military & government, home office & personal use.

Specification

AP-V20U4C19-M16A-LT

Operating Temperature	-5 to 60°C
Storage Temperature	-25 to 70°C
Operating Altitude	0 to 2,000m
Storage Altitude	0 to 15,000m
Humidity	5 to 95% RH, Non-condensing
Protection type	
Universal Outlets - Quantity per breaker	20
Universal - Protection circuit	Banks of 1
Universal - Voltage per socket	230 - 250V
C19 Outlets - Quantity per breaker	4
C19 - Protection circuit	Individual
C19 - Voltage per socket	230 - 250V
Chassis Dimensions (LxWxD)	1702mm x 51mm x 51mm
Net weight	4.9 kg

*Dimension and weight maybe slightly varied