

HDBaseT Extender with KVM - Support 4K@60HZ 4:4:4, Receiver Model : ACE910HR

FEATURES

- Bandwidth up to 18Gbps, resolution up to 4K2K@60hz YUV 4:4:4
- Transmit up to 150m under 1080p,100m under 4K
- Support HDR10
- Support KVM and USB 2.0
- Support Bi-directional wide band IR and RS232 Pass through
- Support Dual POC (Receiver powered by transmitter or transmitter powered by Receiver)
- Support HDCP2.2/ HDCP1.4 Compliant
- Support Copy local and remote EDID functionality
- Supports audio extractor rate up to 192kHz
- Support PCM7.1,Dolby,DTS
- With micro USB port for firmware upgrade



PACKAGE CONTENTS

- Main Unit, operating instruction
- 24V1A DC power supply, 1 x IR RX unit
- 1 Phoenix plugs for RS232 cable termination

SPECIFICATION

Operating Temperature	-5 to +40°C (23 to +104 °F)
Operating Humidity	5 to 90 % RH (no condensation)
Input Video Signal	0.5-1.0 volts p-p
Input DDC Signal	5 volts p-p (TTL)
Video Format Supported	DTV/HDTV; 4K/1080P/1080i/720P(50HZ)/576P/480P/576i/480i
Output Video	HDMI 2.0+HDCP1.4/2.2

Output Audio	Support PCM,DTS-HD, Dolby-HD
Maximum Transmission Distance	150 meters for 1080P, 100 meters for 4K
Poc	Power from TX to RX over Cat5/6 cable
Power Supply	24V1A
Power Consumption	14Watts
Dimensions	172.4mmH×113.2mmW×24mmD
Mass (Main unit)	1.1Kg (Pairs)

HDBaseT Extender with KVM - Support 4K@60HZ 4:4:4, Receiver Model : ACE910HR

CONNECTION DIAGRAM

