

PRO - AV

NEW SOHO H-SERIES



HIGH-END DIGITAL SIGNAGE SYSTEM



Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



4K@60Hz 4x1 HDMI Switch with Multiview Model : AGVS-0401K6

FEATURES

- HDMI 2.0, HDCP 2.2 and backward support
- 18Gbps video bandwidth
- Resolutions support up to 4K@60Hz
- 3.5mm Audio Phoenix Terminal
- Quadview / Dualview / Fullview
- Front panel button / GUI / RS-232
- Seamless switching with Smart EDID
- Super Canvas™ Mode support
- Output up to 7680 x 2160 @ 30Hz
- IR support for remote control
- Drag & Drop support



*SUPER CANVAS™ MODE : Multiple display layouts include quad-view, triple-view, dual-view and full-view. 4 input windows position and size can be adjusted freely with Drag & Drop

SPECIFICATION

Operating Temperature	-10° to 50°C
Operating Humidity	5 to 90%RH (no condensing)
Video Input Connectors	4 x HDMI
Video Output Connectors	1 x HDMI
Data Rate / Pixel Clock	18 Gbps / 600MHz
Audio Output	3p - 3.5mm Phoenix
Resolution Input	3840x2160@60Hz 4:4:4
	- Backward Compatible
Resolution Input	3840x2160@60Hz 4:4:4
Resolution Output	1920x1080@60Hz upto 7680x2160@30Hz or 7680x1080@60Hz

Transmission Distance	5m with standard HDMI cable / 26AWG
Standard	HDMI 2.0/ HDCP 2.2
ESD / Impedance	±4 - 8kV / 100Ω
Down Scale	4K to 1080p
Color Depth	8 bit / 10 bit (Opt)
Control	Button / RJ-45 / RS-232 IR Remote
Power Supply/Consumption	12 V/2.5A 22 W (Max)
Dimension (L x W x H)	280 x 127 x 35 (mm)
Weight	~1 Kg
EDID Control	Smart EDID / Auto

CONNECTION DIAGRAM

