

PRO - AV

NEW SOHO H-SERIES



HIGH-END DIGITAL SIGNAGE SYSTEM



Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:


- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



18G HDBaseT Extender - 150 meters with USB2.0 Model : AHCE-HDU15K6P

FEATURES

- HDMI 2.0b and HDCP 2.2 compliant
- Support 18Gbps video bandwidth
- Resolution up to 4K2K@60Hz YUV 4:4:4
- HDBaseT Mode & Long Reach Mode
- Supports USB 2.0 transmission (HDBaseT mode)
- Bi-directional IR signal and USB KVM
- Support bi-directional POC (Power over Cable)
- Advanced EDID management
- Compact design for easy and flexible installation



PACKAGE	•Transmitter	x 1	•Receiver	x 1	•24V Power Adapter	x 1
	•User Manual	x 1	•IR Cables	x 2	•Mounting	x 4

SPECIFICATION

Operating Temperature	-10° to 50°C
Operating Humidity	5 to 90%RH (no condensing)
Standard	HDMI 2.0b/ HDCP 2.2 USB 2.0 with HDBT Mode*
Transmitter connection	1 x HDMI in/1 x HDBT Out 1 x IR in / 1 x IR Out (3.5mm) 1 x Service (Micro-USB) 1 x USB-B
Receiver connection	1 x HDMI out/1 x HDBT In 1 x IR in / 1 x IR Out (3.5mm) 1 x Service (Micro-USB) 2 x USB-A
Resolution	4K @ 60Hz 4:4:4
Data Rate / Pixel Clock	18 Gbps / 600MHz
IR Level / Frequency	5Vp-p / 20K - 60KHz

Transmission Distance	HDBT Mode: 100m with 4K Long Reach* : 120m with 4K 150m with 1080p
ESD / Impedance	±4 - 8kV / 100Ω
HDR	HDR10, HDR10+, HLG HDR, Dolby Vision
Color Depth	8 - 10 - 12 bit
Audio Format	LPCM 7.1CH, DolbyTrue HD DTS-HD Master
Power Supply/Consumption	24 V/1A 14 W (Max)
Dimension (L x W x H)	65 x 140 x 18 (mm)
Weight	~250gr / unit
EDID Control	Auto

Long Reach* : USB only support HID device in Long Reach Mode
HDBT Mode* : USB support Camera, Storage and other Peripherals.

CONNECTION DIAGRAM

