

PRO - AV

HI-END SERIES



HIGH-END DIGITAL SIGNAGE SYSTEM



Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



3G-SDI to HDMI Converter Model : AHVC-3GHD

FEATURES

- Operation at 2.970Gbit/s, 1.485Gbit/s and 270Mbits/s
- Supports SMPTE 425M, SMPTE 424M, SMPTE 292M, SMPTE 259M-C
- Equalized and re-clocked loop output Integrated audio de-embedder for a maximum of 8 channel, 48 kHz audio
- Conversion from SMPTE 425M level B to Level A 1080p 50/59.94/60 4:2:2 10-bit
- Connect with other units to extend your signal over long distances



SPECIFICATION

Input	1 x BNC (SDI/HD-SDI/3G-SDI)
Output	1 x HDMI
SDI Transmission Rates	2.970 Gbit/s 2.970/1.001 Gbit/s
Power Supply	DC 5V -12V
Dimension	80mm x 41mm x 25mm
Weight	150g
Operating Temperature	0°C ~ 40°C 32°F ~ 104°F

Storage temperature	-20°C ~ 60°C -4°F ~ 140°F
Humidity	20 ~ 90% RH (Non-condensing)
In/Output Resolution	1080p / 60Hz (max)
Power consumption	5W
ESD Protection	Human body model ±8kV (air-gap discharge) & ±4kV (contact discharge)

CONNECTION DIAGRAM

