PRO - AV

NEW SOHO H-SERIES



HIGH-END DIGITAL SIGNAGE SYSTEM



Why choose ANGUSTOS Pro-AV?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- ·Ease-of-use
- ·Design
- ·Innovation
- ·Reliability
- ·Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.





ANGUSTOS PRO AV APPLICATIONS

- Media Telecom Broadcast
- Education Training
- Manufacturing Quality Control
- Retail Advertising
- Meeting Room Conference
- Healthcare visual system
- Entertainment
- Government Control Room











AHVM-H1616P

HDMI 4K@60Hz 16 x 16 MATRIX Model : AHVM-H1616P

FEATURES

- HDMI 2.0b, HDCP 2.2 / DVI 1.0 compliant
- Resolution up to 4K@60Hz (YUV 4:4:4)
- Support 18Gbps video bandwidth
- HDR, HDR10, HDR10+, Dolby Vision
- 4K->1080P Down Scaler for each output port
- HDMI audio pass-through up to 7.1CH HD audio
 (LPCM, Dolby TrueHD and DTS-HD Master Audio)
- Audio de-embedded via coax ports
- ARC, CEC and smart EDID management
- Front panel OLED display
- Buttons, IR remote, RS-232, LAN and Web GUI














SPECIFICATION

| Operating Temperature | -10° to 50°C |
|--------------------------------|---|
| Operating Humidity | 5 to 90%RH (no condensing) |
| Video Input Connectors | 16 x HDMI |
| Video Output Connectors | 16 x HDMI (HDR10/10+) |
| Data Rate / Pixel Clock | 18 Gbps / 600MHz |
| Audio Format Support | LPCM 2/5.1/7.1 |
| | Dolby Digital+, DTS 5.1 |
| | |
| | DTS-HD Master, Dolby Atmos, DTS:X |
| Resolution | DTS-HD Master, Dolby Atmos, DTS:X 4K @ 60Hz |
| Resolution | . , . |
| Resolution Color Space | 4K @ 60Hz |
| | 4K @ 60Hz 1080p@60Hz - Down Scaler |
| | 4K @ 60Hz 1080p@60Hz - Down Scaler RGB, YCbCr 4:4:4 |

| Transmission Distance | 4K@60:5m/@30:10m |
|--------------------------|--------------------------------|
| | 1080p@60:15m |
| Standard | HDMI 2.0/ HDCP 2.2,1.x |
| ESD / Impendance | ± 4 - 8kV $/$ 100 Ω |
| Coax Audio | LPCM 2.0, Dolby Digital/Plus |
| Control | Button / WEB GUI (RJ-45) |
| | IR Remote / RS-232 |
| HDR formats | HDR10, HDR10+ |
| | Dolby Vision, HLG, 3D |
| Power Supply/Consumption | 24 V/3.75A 77 W (Max) |
| | AC 100-240V 50/60Hz |
| Dimension (L x W x H) | 440 x 200 x 44 (mm) |
| Weight | ~3.1kg |
| EDID Control | Auto / Manage |



AHVM-H1616P

HDMI 4K@60Hz 16 x 16 MATRIX Model : AHVM-H1616P

CONNECTION DIAGRAM

