

# PRO - AV

## HI-END SERIES



### HIGH-END DIGITAL SIGNAGE SYSTEM



## Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:


- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



## ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



## 1 x8 HDMI Splitter over UTP Extender 60 Model : AHVS-EH18U7K6

### FEATURES

- HDMI 2.0b, HDCP 2.2 - 1.4 compliant
- 18Gbps video bandwidth
- Resolution up to 4K2K@50/60Hz 4:4:4
- Support HDR, HDR10+, HLG and Dolby vision
- Support up to 7.1CH HD audio pass-through
- Support audio de-embedded output
- Distance up to 35m (4K@60Hz), 50m (4K@30Hz) 60m (1080p@60Hz) with single CAT6/6A cable
- HDMI loop output and 8 CAT outputs.
- One-way IR control signal pass-through
- Advanced EDID management
- Support one-way PoC function (Transmitter to Receiver)



### PACKAGE CONTENT

- \*Base unit(Tx) x 1
- \*Receiver (RX) unit x 8
- \*IR Cable x 8
- \*12V/2.5A Power Adapter x 1

### SPECIFICATION

<b>Standard</b>	HDMI 2.0/ HDCP 2.2
<b>Data Rate / Pixel Clock</b>	18 Gbps / 594MHz
<b>Resolution</b>	4K @ 60Hz 4:4:4
<b>Audio Support</b>	LPCM 7.1CH, Dolby True HD
<b>ESD / Impedance</b>	±4 - 8kV / 100Ω
<b>Transmitter (Base Unit)</b>	1 x HDMI Input, 2x Audio Out 1 x HDMI Out, 8x CAT out, IR
<b>Receiver</b>	1 x HDMI output 1 x IR in, 1 x CAT in
<b>Control</b>	IR out, EDID DIP, Service
<b>HDR Support</b>	HDR, HDR10+, Dolby Vision

<b>Transmission Distance</b>	4K@60Hz: 35m / @30: 50m 1080p : 60m (CAT6/6A)
<b>Color Depth</b>	8/10/12 bit
<b>Power Supply/Consumption</b>	12 V/2.5A   25 W (Max)
<b>POC</b>	Support one-way Directional
<b>Dimension (L x W x H)</b>	300 x 100 x 28 (mm) - Tx 88 x 61 x 18 (mm) - Rx
<b>Weight (gr)</b>	~823 (Tx) / ~155(Rx)
<b>Operating Temperature</b>	0° to 50°C
<b>Storage Temperature</b>	-20° to 60°C
<b>Storage/Operating Humidity</b>	0 to 90%RH (no condensing)

### CONNECTION DIAGRAM

