

PRO - AV

HI-END SERIES



HIGH-END DIGITAL SIGNAGE SYSTEM



Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- Ease-of-use

- Design

- Innovation

- Reliability

- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



K HDMI Switch/Splitter 2 x 8 Model : AHVS-H208K3

FEATURES

- Support 3D
- Resolution up to 3840x2160@30Hz
- 3 Gbps data rate for TMDS clock up to 300Mhz
- Support 8/10/12 bit deep color
- Distant up to 10m (input) - 15m (output) - 1080
- Distant 5m (input) - 10m (output) - 4K
- DC 5V/1A power supply



PACKAGE CONTENT

- ① 1 x Ultra HD Video Wall Processor ② 1 x AC Power Cord ③ 1 x IR Remote ④ 1 x User Manual

SPECIFICATION

Resolution	4K / 1080p down to 480i
Video Color depth	8/10/12 bit
Audio format	LPCM
Max bandwidth	300MHz
Max video rate	3Gbps / channel
Distance support	4K-5m (input)/10m (output) 1080p-10m (input)/15m (output)
HDMI input	2
HDMI output	8
Weight (KG)	640gr
Power	0.7 A

Adapter	100-240VAC. 50/60Hz DC 5V/1A
Operational Temp	-15 to +55°C
Storage Temp	-20 to +60°C
Operational Humid	5-90%RH (No Condensation)
Storage Humid	0-90%RH (No Condensation)
Dimension	278x136x24 (mm)
Operation	Power Button Reset / Select Button IR Remote
*26AWG HDMI Hi-Def Cable	

CONNECTION DIAGRAM

