

# PRO - AV

## HI-END SERIES



### HIGH-END DIGITAL SIGNAGE SYSTEM



## Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



## ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



## Ultra HD Video Wall Processor - 2 x 9 Model : AHVS-H29P

### FEATURES

- HDMI 2.0 and HDCP 2.2 compliant
- Support multi-resolution up to 3840x2160@60Hz video output for video wall
- Support Bezel Compensation with two modes
- Support 2 channels HDMI loop out
- Support PIP on video wal
- Support 180° rotation
- Support RS-232 and TCP/IP control
- Support CEC control with displays by PC Tool or commands



### PACKAGE CONTENT

- ① 1 x Ultra HD Video Wall Processor
- ② 1 x AC Power Cord
- ③ 1 x 5-pin Phoenix Connector
- ④ 2 x 3-pin Phoenix Connector
- ⑤ 1 x User Manual

### SPECIFICATION

<b>Standard</b>	HDMI 2.0/ HDCP 2.2,1.4
<b>RS-232</b>	Baud rate: 57600, data bit: 8, Stop bit: 1
<b>ESD / Impedance</b>	±4 - 8kV
<b>Input</b>	2 x HDMI input
<b>Output</b>	9 x HDMI Out
<b>Audio Format</b>	2.0 channel, 5.1 channel, LPCM, Dolby, AC3, DTS
<b>Dimension (L x W x H)</b>	430 × 220 × 44mm
<b>Weight (KG)</b>	5kg
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Relative Humidity</b>	10%~50% RH (non-condensing)

<b>Input Video Formats</b>	1024x768@60, 1280x800@60,1080p@24 1280x1024@60,1280x960@60,1080p@25 1360x768@60, 1366x768@60,1080p@30 1440x900@60, 1400x1050@60,1080p@50 1600x900@60,1600x1200@60,1080p@60 1680x1050@60, 1920x1200@60,720p@60 480p@60, 576p@50, 720p@50, 1080i@50 1080i@60, 3840x2160@24, 3840x2160@25, 3840x2160@30, 3840x2160@50, 3840x2160@60,4096x2160@24, 4096x2160@30, 4096x2160@50,4096x2160@60
<b>Power Supply</b>	110-220V AC

### CONNECTION DIAGRAM

