

# PRO - AV

## HI-END SERIES



### HIGH-END DIGITAL SIGNAGE SYSTEM



## Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



## ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



## Multipurpose Device - Video Wall - KVM Controller

### Model : AMPD-0808K6G

#### FEATURES

- HDCP 1.4/2.2 and HDMI 2.0
- Seamless video switching with Video Wall
- Support 3840 x 2160 @60Hz 4:4:4
- Support 4096 x 2160 @60Hz 4:4:4
- Support upscale or downscale resolution
- Support LPCM, DD+, DTS, Dolby TrueHD, DTS HD-master pass-through audio
- Advanced EDID management
- Support Web GUI Control
- Front panel Button, IR, RS-232 and TCP/IP
- Status Monitoring
- HDMI Audio de-embedding
- Multi-view mode preset




VIDEO WALL

#### SPECIFICATION

<b>Video Input Connectors</b>	8 x HDMI
<b>Video Output Connectors</b>	8 x HDMI
<b>Audio In/Out Connectors</b>	8 x 3P Phoenix terminal
<b>Standard</b>	HDMI 2.0b/ HDCP 2.2
<b>Data Rate / Pixel Clock</b>	18 Gbps / 600MHz
<b>Input / Output Resolution</b>	3840x2160 @ 60Hz 4096 x 2160 @ 60Hz
<b>Output link resolution</b>	Max 7680X1080@60Hz
<b>HDMI Amplitude</b>	T.M.D.S +/- 0.4Vpp
<b>Differential Impedance</b>	100±15ohm
<b>Control</b>	1 x RS-232 (DB-9) 1 x RJ-45 (web GUI) Buttons

<b>Audio Format Support</b>	DTS-HD Master Audio Dolby True HD, LPCM, DTS, DTS-EX, DTS-96/24
<b>Color Space</b>	RGB, YCbCr 4:4:4 YUV 4:2:0
<b>Color Depth</b>	8 / 10 / 12 bit
<b>Power Supply</b>	AC 100 - 240V 50/60Hz
<b>Power Consumption</b>	100 W (max)
<b>Dimension (L x W x H)</b>	440 x 260 x 45 mm
<b>Operating Temperature</b>	-10° to 60°C
<b>Operating Humidity</b>	0 to 80% RH
<b>Storage Temperature</b>	-20° to 70°C
<b>Storage Humidity</b>	0 to 90% RH

## Multipurpose Device - Video Wall - KVM Controller Model : AMPD-0808K6G




MATRIX SWITCH  
\*WITH SEAMLESS



WEB GUI  
CONTROL




BUILT-IN  
SCALER



MULTI-VIEW  
SUPPORT

### CONNECTION DIAGRAM

#### INPUT



#### OUTPUT

Matrix Switch

### VIDEO WALL MODE SUPPORTED



2x2x2



2x2x1




2x1x2



2x1x3



1x4



4x1x2



2x2x2 Matrix



2x2 Matrix with PiP\*  
(4 output mode)