

PRO - AV

HI-END SERIES



HIGH-END DIGITAL SIGNAGE SYSTEM



Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



Multipurpose Device - Video Wall - KVM Controller

Model : AMVW-0404K3

FEATURES

- 4xHDMI inputs and 4xHDMI outputs
- Input/output video resolution up to 4K@30Hz
- Seamless switching. Support LED/LCD video wall
- Multiview display (with MPiP™ and Roaming)
- Customized output resolution. Backward compatible
- from 720 - 1080p - 4K@30Hz
- 8 Presets save and recall
- Inputs and outputs status monitoring
- Audio de-embedding
- Front panel LCD display with button
- Matrix - Video Wall controller - Multiviewer
- Built-in WEB GUI with Over IP management.
- RS-232 supported



VIDEO WALL

SPECIFICATION

Video Input Connectors	4 x HDMI
Video Output Connectors	4 x HDMI
Audio In/Out Connectors	4 x 3.5mm
Standard	HDMI 1.4/ HDCP 1.4
Data Rate / Pixel Clock	10.2 Gbps / 600MHz
Input / Output Resolution	480p to 4K@30Hz
	Custom resolution*
Output link resolution	3840X1080@60hz
HDMI Amplitude (TMDS)	T.M.D.S +/- 0.4Vpp
Differential Impedance	100±15ohm
Control	1 x RS-232 (DB-9)
	1 x RJ-45 (web GUI)
	IR remote - Buttons

Audio Format Support	DTS-HD Master Audio
	Dolby True HD, LPCM,
	DTS, DTS-EX, DTS-96/24
Color Space	RGB, YCbCr 4:4:4
	YUV 4:2:0
Color Depth	8 / 10 / 12 bit
Power Supply	AC 100 - 240V 50/60Hz
Power Consumption	6W -10W (max)
Dimension (L x W x H)	440 x 160 x 45 mm
Operating Temperature	-20° to 50°C
Operating Humidity	0 to 80% RH
Storage Temperature	-20° to 70°C
Storage Humidity	0 to 90% RH


*Custom Resolution available:

Input: 800x600@60Hz, 1024x768@60Hz, 1280x768@60Hz, 1280x800@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1200@60Hz. 480p/576p/720p/1920x1080i/1920x1080p/3840x2160@24Hz/30Hz

Output: 3840x2160@30Hz, 1280x720@60Hz, 1920x1080@60Hz, 1280x720@50Hz, 1920x1080@50Hz, 1024x768@60Hz, 1920x1080@30Hz, 1920x1200@60Hz, 3840x2160@30Hz.

Multipurpose Device - Video Wall - KVM Controller

Model : AMVW-0404K3




MATRIX SWITCH
*WITH SEAMLESS



WEB GUI
CONTROL




BUILT-IN
SCALER



MULTI-VIEW
SUPPORT

CONNECTION DIAGRAM

INPUT



OUTPUT

Matrix Switch



VIDEO WALL MODE SUPPORTED



2x2





2x1



1x2



1 X 3



Quad-view

Quad-view 2 (With MPiP™)

1 X 2 (With MPiP™)