

# PRO - AV

## HI-END SERIES



### HIGH-END DIGITAL SIGNAGE SYSTEM



## Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



## ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



## HDMI SWITCH - 8 x 1 4K@30Hz with Seamless switch

### Model : ASVS-H0801K3

#### FEATURES

- Support seamless switching
- Manual switching - automatic mode button.
- Output resolution 4K@30Hz/1080P
- Support 24/30/36 bit deep color.
- Automatically switch HDMI input ports \*.
- HDMI input interface time polling function (10/15 second)

\*Auto switch : When HDMI signal is lost, auto switch to HDMI IN 1port  
if IN 1 port is not available, auto scan to IN 2 port, until IN 8 port.



#### PACKAGE CONTENT

- 1 x Switch unit
- 1 x Power Adapter
- 1 x IR Remote



#### SPECIFICATION

Operating Temperature	-10° to 55°C
Operating Humidity	0 to 90% RH
Video Input Connectors	8 x HDMI
Video Output Connectors	1 x HDMI
Input / Output Resolution	4K@30Hz
Data Rate/Pixel Clock-Impedance	10.2 Gbps / 100 Ω
Audio Format Support	PCM
Distance (AWG 26 Cable)	4K: 10m / 1080p : 15m
Control	Button / IR Remote

Standard	HDMI 1.4/ HDCP 1.4
Color Space	RGB, YCbCr 4:4:4
Color Depth	24/30/36 bit
ESD	±8kV (Air-gap discharge) ±4kV (Contact discharge)
Power Supply	AC 100 - 240V 50/60Hz DC 12V/1A
Power Consumption	600 mA (max)
Dimension (L x W x H)	226 x 110 x 25 mm

#### CONNECTION DIAGRAM

