

# PRO - AV

## HI-END SERIES



### HIGH-END DIGITAL SIGNAGE SYSTEM



## Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:


- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



## ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



## HDMI Extender Wireless Dongle - 30 meter Model : AVE-HW30D

### FEATURES

- Transmit wireless video signal up to 30 meters.\*
- Uncompressed audio and video at near-zero latency.
- Resolutions up to 1920 x 1080 @60Hz
- Each RX paired to the unique TX. Plug & Play.
- Private wireless signal (do not need Wi-Fi).
- Digital 60GHz frequency wireless transmission.
- Do not need to install application on mobile / PC
- Pixel Clock 165Mhz . Data Rate 6.75 Gbps  
*\*Wireless transmission distance is greatly affected by environmental factors.*

### SPECIFICATION

<b>Operating Temperature</b>	0° to 60°C
<b>Operating Humidity</b>	0 to 90%RH
<b>Video Input Connectors</b>	1 x HDMI Type A 1 x USB Type-A (Power)
<b>Video Output Connectors</b>	1 x HDMI Type A 1 x USB Type-A (Power)
<b>Data Rate / Pixel Clock</b>	6.75 Gbps / 165MHz
<b>Resolution Support (max)</b>	1920x1080p@120Hz
<b>Transmission Frequency</b>	2.4 G / 5 G - Private

<b>Transmission POV</b>	180°
<b>Delay</b>	5 - 20ms depend on range
<b>Power / Consumption</b>	DC 5V - 600mA / 3W
<b>Transmission Range</b>	20-30m open area
Range is limited with obstacles in room	

#### Package include

- \* Receiver (RX) x 1
- \* Transmitter (TX) x 1
- \* Manual x 1



Wireless



Private Link



30m

### CONNECTION DIAGRAM

