

PRO - AV

NEW SOHO H-SERIES



HIGH-END DIGITAL SIGNAGE SYSTEM



Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:


- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



4K HDMI Extender 50 meters - ARC Model : KVE805K6

FEATURES

- HDMI2.0/ DVI 1.0 and HDCP 1.4/2.2 compliant
- Support 18Gbps video bandwidth
- Support video resolution up to 4K2K@60Hz 4:4:4
- Distance up to 50m (Cat5E) or 60m (Cat6/6A) single.
- Support HDMI Loop Out
- Support one - way IR control
- LPCM 7.1, Dolby True HD, DTS HD Master
- EDID copy pass-through
- Support HDR features
- Support bi-directional POC



PACKAGE

IR transmitter	x 1	Transmitter unit	x 1
IR receiver	x 1	Receiver unit	x 1
User Manual	x 1	12V Power Adapter	x 1
		Mounting	x 1

SPECIFICATION

Standard	HDMI 2.0/ HDCP 2.2-1.4
Data Rate / Pixel Clock	18 Gbps / 600MHz
Resolution	4K @ 60Hz 4:4:4
Audio Support	LPCM 7.1CH, Dolby True HD
ESD / Impedance	±4 - 8kV / 100Ω
Transmitter	1 x HDMI input, Service 1 x HDMI out, IR, CAT out
Receiver	1 x HDMI output IR, CAT in, Service
Control	IR in / IR out
HDR Support	HDR10

Transmission Distance	4K@60Hz : 50-60m 1080p : 70m (CAT6/6A)
Color Depth	8/10/12 bit
Power Supply/Consumption	12 V/1A 4 W (Max)
POC	Support Bi-Directional
Dimension (L x W x H)	88 x 61 x 18 (mm)
Weight	~160gr
Operating Temperature	0° to 50°C
Storage Temperature	-20° to 60°C
Operating Humidity	0 to 90%RH (no condensing)
Storage Humidity	0 to 90%RH (no condensing)

CONNECTION DIAGRAM

