

HDMI Matrix Switch 4x4, 4K@60HZ 4:4:4 Model : KVM0404K6P

FEATURES

- Support 4K@60Hz YUV4:4:4
- Support 3D, Support HDR10
- Bandwidth upto 18Gbps
- HDCP2.2 input ,HDCP2.2 output
- HDCP1.4 input, HDCP1.4 output
- 4xHDMI Input, 4xHDMI output with 4xSPDIF Audio
- Any one of the 4 Ultra HD sources to any one of the 4 Ultra HD displays
- Support Panel Button, Local IR, RS232 Control with command, IP Control, Web GUI Control
- Support Dolby True HD and DTS-HD master audio



SPECIFICATION

Bandwidth	18 Gbps
Resolution	4K@ 60hz YUV4:4:4, 1080P@60hz
Video Input Connectors	4xHDMI
Video Output Connectors	4xHDMI
RS-232 serial port	3 PIN terminal block connectors
Ethernet port (IP control)	RJ45, female
IR Ext port	1x3.5mm stereo jack

Audio Format Supported	PCM, Dolby 7.1, DTS 7.1, Dolby Atmos
Rack-Mountable	Rack ears included
Operating Temperature	23°F to 113°F (-5°C to 45°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Dimension (L×W×H)	216 x 105 x 34mm
Power consumption	13W(MAX)
Net Weight	0.72kg

CONNECTION DIAGRAM

