### PRO - AV

NEW SOHO H-SERIES



### HIGH-END DIGITAL SIGNAGE SYSTEM



### Why choose ANGUSTOS Pro-AV?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- ·Ease-of-use
- ·Design
- **Innovation**
- ·Reliability
- ·Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.





# ANGUSTOS PRO AV APPLICATIONS

- Media Telecom Broadcast
- Education Training
- Manufacturing Quality Control
- Retail Advertising
- Meeting Room Conference
- Healthcare visual system
- Entertainment
- Government Control Room













## **HDMI 4K SPLITTER** Model: KVS104K6P

### **FEATURES**

- HDMI 2.0, HDCP 2.2 standards.
- Resolution 4K UHD@60Hz 4:4:4.
- 3D Frame format up to 4K2K@30Hz
- VESA format up to QSXGA@60Hz
- DTS-HD Master Audio up to 7.1CH.
- LPCM 7.1CH, Dolby TrueHD
- Smart EDID management.
- 8 bit RGB/YCBCR 4:4:4/YCBCR 4:2:2
- EDID Switch for TV (Copy Out1) or STD

#### **PACKAGE**

**HDMI Splitter unit** x 1 x 1 **Power Adapter** 













### **SPECIFICATION**

<b>Operating Temperature</b>	-10° to 50°C
Operating Humidity	5 to 90%RH (no condensing)
Video Input Connectors	1 x HDMI
<b>Video Output Connectors</b>	4 x HDMI
Data Rate / Pixel Clock	18 Gbps / 600MHz
<b>Audio Format Support</b>	LPCM 7.1 CH, Dolby True HD
	DTS-HD Master Audio
EDID Control	Auto   TV - STD Switch

Transmission Distance	5m with standard
	HDMI cable / 26AWG
Standard	HDMI 2.0/ HDCP 2.0
Max Resolution	4K2K @ 60Hz
Power Supply/Consumption	5 V/1A   2-3 W (Max)
Dimension (L x W x H)	63 x 163 x 16 (mm)
ESD / Impendance	$\pm 4$ - 8kV $/$ 100 $\Omega$

### CONNECTION DIAGRAM

