

PRO - AV

NEW SOHO H-SERIES



HIGH-END DIGITAL SIGNAGE SYSTEM



Why choose ANGUSTOS Pro-AV ?

We can provide you the best solution that suits your TVs, interactive screens, meeting room high-end projector, digital signage and videowall system. We do not just simply sell the equipments but also a smart solution that is just as well designed as it is functional. Solutions that guarantee and define our brand:

- Ease-of-use
- Design
- Innovation
- Reliability
- Ease-of-installation.

To help you find the exact solution you need, Angustos has an extensive product range that is possible to compose a solution for nearly every Pro AV application. Our highly skill solution teams are happy to help you to quickly find the best solution for your installation, saving you the time and effort and hassle for complex system.



ANGUSTOS PRO AV APPLICATIONS

- Media - Telecom - Broadcast
- Education - Training
- Manufacturing - Quality Control
- Retail - Advertising
- Meeting Room - Conference
- Healthcare visual system
- Entertainment
- Government - Control Room



4K@60Hz 4x1 HDMI Switch with Multiview Model : KVSMQ0401K6

FEATURES

- HDMI 2.0b, HDCP 2.2 and backward
- 18Gbps video bandwidth
- Resolutions support up to 4K@60Hz
- LPCM, AC3, DD+, DTS, DTS-HD
- Support 7.1 audio channel
- Seamless switching
- Up to 8 display modes
- Audio de-embedding analog & optical
- Volume control and independent audio
- EDID management
- Front panel buttons, OSD
- RS-232 with IR Remote




PACKAGE

IR remote	x 1	HDMI Switch unit	x 1
IR receiver	x 1	12V Power Adapter (AC 100-240V 50/60Hz input)	x 1
User Manual	x 1	Mounting Ear	x 1

SPECIFICATION

Operating Temperature	-10° to 50°C
Operating Humidity	5 to 90%RH (no condensing)
Video Input Connectors	4 x HDMI
Video Output Connectors	1 x HDMI
Data Rate / Pixel Clock	18 Gbps / 600MHz
Audio Output	1 x L/R (RCA) 1 x Optical (S/PDIF)
Audio Format Support	PCM 2.0 / 5.1 / 7.1 Dolby Digital/Plus/EX Dolby True HD, DTS, DTS-EX
Resolution	4K @ 60Hz 4:4:4 RGB, 4:2:0, 4:2:2

Transmission Distance	10m with standard HDMI cable / 26AWG
Standard	HDMI 2.0b/ HDCP 2.2
ESD / Impedance	±4 - 8kV / 100Ω
Down Scale	4K to 1080p
Color Depth	8 bit / 10 bit (Opt)
Control	Button / RS-232 IR Remote
Power Supply/Consumption	12 V/2.5A 10 W (Max)
Dimension (L x W x H)	105 x 220 x 44 (mm)
Weight	~650gr
EDID Control	Auto



QUAD VIEW - 2

CONNECTION DIAGRAM

