4K - UHD

Video Wall Controller



4K-UHD FPGA VIDEOWALL CONTROLLER



Hardware Based Design

hardware architecture design.

No more computer high-end specification.

No more high-end GPU Card.

No more licenses. 🖈

No more blue-screen OS crash.★

No more viruses and black screen. No more ransomwares, lost data,

Support up to 72 input x 72 output.



High performance video processing equipment with *



FPGA Dedicated Chipset

Dedicated Field Programmable Gate Array (FPGA) chipset is a combination of processing unit that dedicated in video processing. This eliminated the limitation of a CPU or a GPU from conventional Software or PC controller.

Without the use of PCI - Express card, the unit can work flawlessly when adding or editing the total layout of the videowall set up. As each of the FPGA chip is working independently, user can replace or add new input/output card to customize their system.

Features

Modular design - Mix and Match

 4×4 up to 72×72 input x output slot with mixing ports

Easy control with Drag & Drop

Customize complex layout with simple Click - Drag - Drop

4K Video Wall with Flexible set up

Support DVI-I / HDMI / 3GSDI / HDBaseT / Fiber connections. Support resolution up to 4K@6OHz for both input / output (HDMI)

Built-in Audio port

Support 3.5mm audio embedded and de-embeded function

Specialized video setting

Support HDMI 1.4 with HDCP 2.2 / 1.4 Edge Shield features for Bezel pixel compensation in Video Wall setting

Scaling function

Support up/down scaling function via the DIP switch

Seamless Switching

Switching speed can reach 32Gbps

Module design with Hot Swap

Multiple form of connections for client to custom fit their system. Client can now combine HDMI - DVI - VGA - HDBaseT & IP Streaming in one total solution, maximizing system integration.

Reduce total cost of investment in both pre/post phase of expansion. Chassis also support control over Remote control, TCP/IP, RS-232 & button, further simplify the complexity of connections and management.





VIDEO WALL CONTROLLER with SEAMLESS - AMC Series 04 x 04 Ultra HD Resolution - 4K@60Hz Video Wall

Features

- Pure Hardware Structure FPGA
- Modular Design with Video Wall.
- Seamless Switching Flex EDID
- Multiple format I/O Card
- Mobile apps Support
- RS-232 control support
- Easy manage with TCP/IP
- Drag&Drop with Preset support
- Support Edge Shield Benzel adjust
- Support cable up to 25m

MATRIX Soft base of the potential of the

SPECIFICATION

Chassis size	1 U
Max. Data Rate	32 Gbps (12.5Gbps per Lane)
Input Interface Port	1 to 4 (Modular)
Output Interface Port	1 to 4 (Modular)
I/O Interface Support	DVI-I / HDMI / 3G-SDI / HDBaseT
	VGA/Optical Fiber / CVBS / YPbPr
Control	Button/IP / RS-232 / Mobile App (Option)

HDCP	Support 1.3 / 1.4 / 2.2
EDID	Auto - Program
HDMI protocol	Support up to HDMI 2.0 with audio
Resolution Input	480p up to 4096x2160 @ 60 Hz
Resolution Output	480p up to 4096x2160 @ 60 Hz
Scaler	Support both up/down scaling
Power	200W, 110 ~ 260V, 50-60 Hz
Temp / Humid	-20°C ~ + 60°C / 0% ~ 95%
Temp / Humid Storage	-25°C ~ + 65°C / 0% ~ 95%

