

Camera Dome - Artificial Intelligent ICR-DC2SAI

Features

- 3.0MP SONY
- Board Lens: 2.8 mm
- Night vision: 30M
- IP 67 - Weather Proof Metal Housing.
- Artificial Intelligent Chipset
- Support P2P Cloud Service
- Support ONVIF V2.4 Standard Protocol
- Internal / External POE / Power Adapter Option



Camera SPEC

Image Sensor	1/2.8" SONY
Resolution	3.0 Mega Pixel (1080P)
Effective Pixels	2048*1536P
Compression	H.264/H.265
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec NTSC 1/30-1/10000Sec
Usable Illumination	0.001Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Support
Video Delay	0.3S (Within the Lan)
Frames Per Second	30Fps

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR White Balance, BLC, FLK
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
WDR	DWDR
Recording Mode	NVR/NAS/CMS/Web
Focus Length	2.8mm
Focus Control	Fixed
Infrared LED	2PCS SMT LED
Infrared Distance	30M

General

Housing	Metal
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	89x90mm
Weight	0.4kg