

RAPTOR-6KRT/RAPTOR-10KRT



Overview

The high-quality online double-conversion UPS that offers the ideal power protection for heavily loaded equipment

Designed for office and data center applications, the RAPTOR Series adopts double-conversion topology to provide seamless Pure Sine Wave output. The products are compatible with generators to prolong power continuity. The UPSs also adopt ECO Mode to help save on energy costs, Smart Battery Management (SBM) to extend battery lifespan, and multifunction LCD readout to display precise information. The power management software allows users to easily control and monitor the UPS system.

Features

- N+X parallel redundancy, support maximum 4 units in parallel
- Online double conversion with full digital control
- Optimization battery group, the quantity of battery: 16/18/20pcs (Settable)
- Wide input voltage range: 110~286Vac
- Wide input frequency range
- Selectable output voltage: 208/220/230/240Vac
- Generator compatible
- ECO mode operation for energy saving
- Self-testing when UPS startup
- Multiple communication interface: RS232/USB/EPO (Relay card/SNMP card optional)
- Maximum charging current up to 10A
- Cold start
- Design with maintenance switch (Optional)
- Intelligent fan speed regulation
- Multiple protection function: short-circuit, overload, overheat, battery overcharge and overdischarge, output low voltage and fan fault alarm


Application

Raptor 6~10kVA, Rack/Tower models application areas

- Data Network: Mid - range Servers (Windows and Linux), Wi-Fi Applications & Data networks
- Small Data Center Rooms
- Voice Networks: Cellular Sites, Voice Over IP (VOIP), Very small Aperture Terminals (VSAT) PBX And IT-enabled PBX Automation industries
- Process Automation Equipment: Programmable Logic Controllers (PLS) and Cash Machines (ATM)

Advanced protection for :

- Infrastructure
- Industrial and Medical IT
- Networking
- Storage
- Telecom



Online (Double Conversion) UPS Topology



Extended Battery Module (EBM)



Zero Transfer Time



Remote Management Capability



Smart Battery Management



UPS Parallel Expansion



ECO Mode



Generator Compatible

Angustos

Angustos was founded in 2000 and is now regarded as one of the foremost manufacturers of Uninterruptible Power Supply, IT equipments,...

For more than 20 years our customers have been convinced by our core competencies in extending, switching and distributing standardised computer signals.

We are committed to established international standards. We can provide customers with complete Datacenter & Power solutions as well as OEM/ODM services. We can cover even from medium to small business, factory & industrial, military & government, home office & personal use.

Model Name	RAPTOR-6KRT		RAPTOR-10KRT	
Power Rating	6 kVA / 5.4 kW		10 kVA / 9 kW	
GENERAL				
UPS Topology	Online Double Conversion			
ECO Technology	Online ECO Mode Efficiency > 96%			
Parallel Expansion	Max. Units up to 4			
Active PFC Compatibility	Yes			
INPUT				
Nominal Voltage	208/220/230/240Vac ±10%, Single Phase			
Input Voltage Range	110~286Vac			
Rated Input Current (A)	27.3A		45.5A	
Power factor	≥0.99			
Frequency Range	40~70Hz (50/60Hz, 50±10Hz, 60±10Hz)			
Frequency Detection	Auto-sensing			
Input Connector type	Hardware Terminal Block			
OUTPUT				
Voltage	208/220/230/240Vac, Single Phase			
Voltage Regulation	±1%			
Output Voltage Setting	Configurable			
Output Frequency	(50 ± 0.1%, 60 ± 0.1%)Hz			
Power Factor	0.9			
Overload Protection	Internal Current Limiting, Circuit Breaker, Fuse			
Overload Protection (Line Mode)	105~125% Load for 10 min, 125~150% Load for 1 min, 150~170% Load for 10 sec, >170% Load for 1 sec			
Overload Protection (Battery Mode)	105~125% Load for 2 min, 125~150% Load for 30 sec, >150% Load for 1 sec			
Overload Protection (Bypass Mode)	125~150% Load for 1 min, 150~170% Load for 10 sec, >170% Load for 1 sec			
Harmonic distortion	THDv < 2% Linear load, THDv < 5% Non linear load			
Efficiency AC-AC	Up to 94%			
Output Connector type	Hardware Terminal Block			
BATTERY				
Voltage	240VDC			
Runtime@50% Load(min)	17		11.5	
Runtime@100%Load(min)	6.5		4.5	
Typical Recharging Time	6-7 hours			
Charging current (Max.)	10A (settable base on battery capacity)			
INDICATORS				
LED display	Battery mode, Line mode, Bypass mode, ECO mode, Battery low voltage, Overload & UPS fault			
LCD display	Input frequency, Input voltage, Output frequency, Output voltage, Load percentage, Battery voltage, Inner temperature & Remaining battery backup time			
Alarm	Battery mode : beeping every 4 seconds; Battery low : beeping every second; Overload : beeping twice every second; Fault : continuously beeping			
PHYSICAL & STANDARDS & ENVIRONMENT				
Dimension(WxDxH)/Weight	440 × 685 × 217.5 mm / 74kg (5U)		440 × 625 × 217.5mm / 76kg (5U)	
SAFETY	IEC/EN 62040-1, IEC/EN 62477-1			
EMC	IEC/EN 62040-2 (IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11, IEC 61000-2-2)			
Environment	Operating temperature : 0°C - 40°C; Storage temperature : -25°C~55°C; Humidity range : 20~95%RH @ 0~40°C (Non condensing) Altitude : < 1500m, derating required when >1500m; Noise level < 55dB @1 Meter with 6kVA & < 58dB @1 Meter with 10kVA			

1. When output voltage is 208Vac, need to derate to 80% of the unit capacity
2. Specifications are subject to change without prior notice
3. Data above are typical values for reference only, not as a basis for engineering design

Raptor Series 6-10kVA Rack/Tower Models Battery Pack Specification

Model Name	RAPTOR-BPSVN		RAPTOR-BPNNE	
GENERAL				
Battery Type	VRLA (Lead acid maintenance free battery)			
Battery recharging time	6-8 hours (To 90% of full capacity)			
Typical battery life	3-5 years, depend on discharging cycle and ambient temperature			
System voltage	240VDC			
Battery quantity	1×20 PCS			
Capacity	7Ah x 12V		9Ah x 12V	
PHYSICAL				
Dimension W×D×H	440×680×131mm (3U)			
Net weight	58kg		63kg	
ENVIRONMENT				
Safety	CE			
Operating environment	0°C - 40°C			
Relative humidity	0~95% (Non condensing)			
Noise level	< 40dB at 1 Meter			

Note: Specifications are subject to change without prior notice