

Rackmount - 8 Port CAT5 KVM Switch AR-UV08L

Features

- Control 8 computers with local
- Both the console and the computer are compatible with PS/2, USB
- Computer selection via front panel switches and OSD.
- Auto Scan Mode for monitoring all computers.
- Superior video quality.
- Hot pluggable – add or remove computers for maintenance without powering down the switch
- Support Windows, Solaris etc



KVM SWITCH

| | | |
|-----------------------------|--|--|
| Direct Computer Connections | 8 | |
| Cascade(Max) | 128 | |
| CPU Port Selection | OSD Menu, Front Panel Remote Control IP (Optional) | |
| Console | Monitor | 1 xHDB Female(Blue) |
| | Keyboard | 1 x USB Type A Female 1 x PS2 Female (Purple) |
| | Mouse | 1 x USB Type A Female 1 x PS2 Female (Green) |
| | Expansion Interface | 1 x USB Type A Female |
| PC Connector | Monitor, Keyboard/Mouse Switch Module | 8 x VGA DB15 Female Blue, 8 x USB Or 8 x PS/2 |
| | Switch Module Port | 8 x RJ45 |
| Power | 1 x DC | |
| Network Port | 1 x RJ45(Optional) | |
| Connection Port Selection | KVM Operation Panel Digital | |
| KVM Reset | 1 x Semi-embedded keys | |
| IP Module Reset | 1 x Semi-embedded keys | |
| IP Module Default | 1 x Semi-embedded keys | |

| | |
|-----------------------------|-------------------------------|
| Computer Selection Port | 8 x Green |
| On Line | 8 x Red |
| IP Module Network Interface | 1 x Green, 1 x Orange |
| Analog Mode | USB, PS2 |
| Video resolution (Max) | 1920 x 1200 @ 60HZ |
| Scan time interval | 3, 5, 10, 15, 20, 30, 40, 60s |

OPERATIONAL SPECIFICATION

| | |
|----------------|--------------------------|
| Operating Temp | -10°C - 50°C |
| Storage Temp | -20°C - 60°C |
| Humidity | 0-80%RH, No Condensation |

PHYSICAL SPECIFICATION

| | |
|-----------|-------------------|
| Housing | Metal |
| Dimension | 432 x 155 x 44 mm |
| Weight | 1.82KG |