


High-End KVM



HIGH-END KVM SWITCH



No-Edged KVM™



Switching between multiple PC has never been easier with Angustos Innovated No-Edged KVM™ features. User can just simple moving the mouse cursor to next screen. No button, no clumsy hot-key needed. Support up to 4 PC with one KVM unit.



AC-USB2U
AC-USB4U



AD-D41QU : 4 Port DVI Multi-View




AD-HM133
HDMI KVM Over IP



AD-H41QU : 4 Port HDMI Multi-View



One-Glance KVM™



It's easy to set up multiple monitors to work with one PC, but it's very difficult to blend 4 PC to work with one monitor. With Angustos new One-Glance KVM™ technology, user can now set up to work with 4 different PC in just one monitor. Everything is just in one glance!



Multiple - Session Over IP KVM

Supports advanced features to maximize the server management capability such as remote power control over serial port, time zone and time synchronization, Including full 1024-bit PKI user authentication, 256-bit SSL data encryption, LDAP, RADIUS, Active Directory Servers, and RADIUS. This lines is functionally versatile, robust, and ultra-secure, truly your best choice for advanced enterprise server management needs.



Desktop KVM - LCD KVM

Complete wide range of Desktop KVM and LCD KVM Switch Support common DB-15 KVM port and High Density Cat 5/6 port Support High Density up to 32 ports on each units, cascadable.



*Short Depth Version Option



KEYBOARD & MOUSE

Keyboard	100 Keys, Detachable
Compatible	Windows XP / 7 / 8 / 10
Mouse	Touchpad
Mouse Resolution	>1000 dots/inch (40x40/mm)
MTBF	1,000,000 Press

KVM SWITCH MODULE

Direct PC connection	4 / 8 / 16 / 32
Maximum PC Connection	128 / 256 / 512
Port Selection	OSD, Button, Hot Key
Console Connector	VGA / DVI / HDMI
KVM Connector	DB-15 / RJ-45 Ports
Power	DC Jack
Switch button	Panel Digital Keys
Reset Switch	Panel Function Keys
Status LEDs	Nixie Tube (Selected Port)
	Red led (Online Port)

LCD MONITOR

Ratio	17"/18.5"/19" 4:3 / 16:9
Video	Wide AHVA TFT - LCD
Visible Square	409.8 H x 230.4 V
Resolution	1920 x 1080 @ 60Hz
Color	16.7 Mil, True 8 Bit
Contrast	1000 : 1 (Typ)
Back light	LED Screen
Pixel Pitch	300 x 300 um
MTBF	100,000 hours

OPERATIONAL SPECIFICATION

Operating Temp	-10°C - 50°C
Storage Temp	-20°C - 60°C
Humidity	0-80%RH, No Condensation