

## Camera Speed Dome PTZ - Artificial Intelligent SDR-DC2X40

### Features

- 2.0MP SONY
- Board Lens: 6mm - 96mm. 40x optical zoom
- Night vision: 120M
- IP 67 - Weather Proof Metal Housing.
- Built in two way audio function, intrusion warning prompt
- Support P2P Cloud Service
- Support ONVIF V2.4 Standard Protocol
- Support POE / Power Adapter Option



### Camera SPEC

Image Sensor	1/2.9" SONY
Resolution	2.0 Mega Pixel (1080P)
Effective Pixels	1920 x 1080P
Compression	H.264/H.265
TV System	PAL/NTSC
Audio	Built-in Two way Audio
Usable Illumination	0.01 Lux
S/N Ratio	≥50dB
Scanning System	Progressive
Video Output	Network

### Camera Features

Horizontal Rotation Range	0°~360°
Vertical rotation	0° ~ 93°
Horizontal rotating speed	80°/ SEC
Vertical rotation speed	60°/ SEC
Recording Mode	NVR/NAS/CMS/Web
Focus Length	6mm - 96mm
Focus Control	Fixed
Infrared LED	14μ x 18PCS
Optical Zoom	40x Optical Zoom

### Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Support
Video Delay	0.3S (Within the Lan)
Frames Per Second	25Fps

### General

Housing	Metal
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 3A
Dimension	310 x 301 x 440 mm
Weight	10.2kg