


2x2 HDMI Videowall Controller Model : AFVW22K

FEATURES

- 2 x 2 Screens Processing with Presets
- 4 switchable sources: Type-C, DVI, or HDMI.
- Cascading up to a 10x10 video wall
- 4K @30Hz for HDMI and Type-C inputs
- Supports 180° image rotation
- Edge correction, HDMI loopout
- SPDIF Coaxial and Analog audio extraction
- 5.1-channel audio (HDMI input)
- Panel buttons, IR remote, RS-232, Web GUI control
- FCC, CE and RoHS compliant



SPECIFICATION

Operating Temperature	-0° to 40°C
Operating Humidity	5 to 90%RH
Video Input Connectors	HDMI x 2 DVI, USB-C
Video Output Connectors	5 x HMDI Type A
Video Wall Mode	1 x 1 2 x 2 4 x 1 1 x 4 3 x 2 4 x 2 4 x 4 ... Stackable max 10 x 10

Ethernet Ports (IP control)	RJ45, Female.
Video / DDC Signal	0.5-1.0 / 5 volts p-p (TTL)
Audio Format	LPCM 16-24bit 44.1-48KHz
Resolution	4K@30Hz 1080p
Power Consumption	15W (Max)
Dimension (L x W x H)	438 x 190 x 44
Control	Web RS-232 Panel Remote

CONNECTION DIAGRAM

